



NEW
 Auto-EPAP, HFNT,
 AHI plus built-in
 humidifier with
 heated wire
 circuit



Vivo 45LS – Innovation for better breathing and quality of life.

The Vivo 45LS life support ventilator maximizes patient mobility and breathing comfort. It features a built-in humidifier with heated wire circuit, plus a comprehensive set of modes that includes Auto-EPAP and High Flow Nasal Therapy plus SpO₂, EtCO₂, FiO₂ and PtcCO₂ monitoring.

PATIENT COMFORT

- Whisper Quiet operation (<30 dBA)
- eSync's patented inspiratory trigger minimizes uncomfortable auto-triggers caused by leaks and may promote increased compliance
- Vivo Auto-EPAP operates without oscillations, maneuvers, test breaths or test pulses

IMPROVED CLINICAL WORKFLOW

- Built-in Humidifier for NIV with heated wire circuit saves space and expense
- VAPS + AE Mode

Setting
 the NEW
 Standard

MOBILITY

- Ultra-small and Lightweight
- Up to 24+ hour* Battery Life

PATIENT DATA PROMOTES INFORMED CLINICAL DECISIONS

- Remote connectivity to EveryWare
- Early interventions from monitoring of SpO₂, FiO₂, etCO₂, and PtcCO₂,
- AHI Calculation

GETTING PATIENTS HOME

- High Flow Nasal Therapy
- 3 easy-to-use profiles adapt to patient activities



Breas Vivo 45LS Technical Specifications

Settings / Performance	
Ventilation Modes	PSV, PSV(TgV), PSV(AE), PSV(TgV+AE), PCV, PCV(TgV), PCV(A), PCV(A+TgV), PCV(A+AE), PCV(A+TgV+AE), PCV-SIMV, PCV-MPV, VCV, VCV(A), VCV-SIMV, VCV-MPV, CPAP, HFNT
Patient Modes	Adult, Pediatric
Device Modes	Home, Clinical
Profiles	3 settable profiles
Inspiratory Pressure	4 to 50 cmH ₂ O, max PS of 30 cmH ₂ O above PEEP (Pediatric)
PEEP	2 to 20 cmH ₂ O, IPAP -2 cmH ₂ O or Min IPAP -2 cmH ₂ O
Auto-EPAP (Expiratory Positive Airway Pressure)	2 to 20 cmH ₂ O
Breath Rate/Backup Rate	4 - 40 bpm (Adult), 6 - 60 bpm (Pediatric)
Inspiratory Time/Backup Insp. Time	0.3 to 5 s (Adult), 0.3 to 2 s (Pediatric)
Rise Time	1 to 9 (PSV & PCV), 50 to 90%, Off (VCV)
Inspiratory Trigger	1 to 9 (PSV & PCV, VCV), Off (PCV, VCV)
Expiratory Trigger	1 to 9
Minimum Inspiratory Time	Off, 0.3 to 3 s (Adult), Off, 0.3 to 2 s (Pediatric)
Maximum Inspiratory Time	0.3 to 5 s, Off (Adult), 0.3 to 2 s, Off (Pediatric)
Tidal/Target Volume	Off, 300 - 2000 ml (Adult), Off, 50 - 400 ml (Pediatric)
High Flow Nasal Therapy	4 - 60 lpm
Monitoring	
Displayed data	Ppeak, PEEP, Pmean, Leakage, MV, Vt, FiO ₂ , % in TgV, Total Rate, Spont Rate, % Spont, SpO ₂ , Pulse Rate, I:E, Inspiratory Time, Rise Time, EtCO ₂ , InspCO ₂ , PtcCO ₂ , Flow, AHI
Waveforms	Pressure, flow, volume, EtCO ₂ , leakage
Trends over 1, 6, 24, 48 h and 10 days on device screen	SpO ₂ , Ppeak, PEEP, Total Rate, Spontaneous Rate, Leakage, Vte, EtCO ₂ , Flow
Power Supplies	
Mains supply	100 to 240 V AC
External DC	19 V ± 6 V
Click-in battery	5.5 hours
Internal battery	2 hours
External Xpac Li-ion battery pack	18 hours
Main alarms	
Alarms	High Pressure, Low Pressure, High PEEP, Low PEEP, High Vti, Low Vti, High MVi, Low MVi, High Vte, Low Vte, High MVe, Low MVe, High Breath Rate, Low Breath Rate, Apnea, Disconnection, Rebreathing, Obstruction, High FiO ₂ , Low FiO ₂ , High SpO ₂ , Low SpO ₂ , High EtCO ₂ , Low EtCO ₂ , High InspCO ₂ , High Pulse Rate, Low Pulse Rate, PtcCO ₂ , Power Fail, High Patient Air Temp, Low Patient Air Temp, Low Last Power Source, Crit. Low Last Power Source, Lost Mains Power, Exhalation Valve Control Error, SpO ₂ Disconnection, SpO ₂ Signal Lost, Poor SpO ₂ Signal, CO ₂ Disconnection, CO ₂ Accuracy, Check CO ₂ Adapter, CO ₂ Sensor, FiO ₂ Disconnection
Dimensions	
W x H x D	8.50" x 6.26" x 5.98" (216 x 159 x 152 mm)
Weight	5.3 lb (2.4 kg)
Noise level (at 10 cmH ₂ O constant pressure)	Less than 30 dB(A)
Connectivity and Software	
Built-in connectivity	Ethernet, USB and iLink (plug-in)
Treatment follow up	EveryWare Cloud solution by Breas, PCSW
Plug-and-Play accessories	SpO ₂ , PtcCO ₂ , EtCO ₂ , FiO ₂ , Nurse Call, Remote Alarm, Remote Start/Stop
Other	
Humidification	Integrable water chamber
Circuits	Leakage Circuit, MPV Circuit, Circuit with Active Exhalation Valve, and proprietary Heated Wire Circuit

*Based on combined usage times of internal, click-in, and Xpac external batteries.

Intended use: The Vivo 45LS ventilator (with or without the SpO₂ and CO₂ sensors) is intended to provide continuous or intermittent ventilatory support for the care of individuals who require mechanical ventilation. Specifically, the ventilator is applicable for pediatric through adult patients weighing more than 5 kg (11 lbs.), however, the mouthpiece ventilation modes are for adult patients only. The Vivo 45LS with the SpO₂ sensor is intended to measure functional oxygen saturation of arterial hemoglobin (%SpO₂) and pulse rate. The Vivo 45LS with the CO₂ sensor is intended to measure CO₂ in the inspiratory and expiratory gas. The device is intended to be used in home, institution, hospitals and portable applications such as wheelchairs and gurneys. It may be used for both invasive and non-invasive ventilation. The Vivo 45LS is not intended to be used as an emergency transport or critical care ventilator.

Vivo by Breas, Breas, EveryWare by Breas, eSync and the Breas logo are trademarks of Breas Medical AB. © 2026 Breas Medical - All rights reserved. Breas Medical reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Breas representative for the most current information. BOS-MAR-MAR-000506 Rev 9

Breas Medical Inc · 16 Esquire Rd · N. Billerica · MA 01862 · USA · Phone 855-436-8724 · www.breas.us